















BUILDING PRODUC delivering solutions

The glazing system explained

The H-Bar system makes handling and installation easy and flexible. The Multiwall sheets simply slot into the H-Bar ready for fixing to the structure. The glazing bar system allows for thermal expansion and eliminates the need for penetrations through the sheet, making the structure watertight.

GAUGE 10mm



Standard Lengths

2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 9.0 metres

Standard Width

1050mm

Standard Colours

Clear, Bronze Tint, Grey Tint, Platinum, Opal

Sheet Weight

1.7 kg/m²

Other colours, gauges, widths and lengths available. Lead times may apply.

Accessories

Aluminium Edge Bar Standard Colours: Mill Finish, Black, White Standard Length: 6m Easy slot in installation.



Use to start and finish H-Bar assembly.

Aluminium One Piece H-Bar


Standard Colours: Mill Finish, Black, White Standard Length: 6m Easy slot in installation. Recommended for high wind areas.

Aluminium Two Piece H-Bar

Standard Colours: Mill Finish, Black, White Standard Length: 6m Join and Cover edges of Multiwall sheets. Enables ease of sheet replacement.

Aluminium End Cap

Standard Colours: Mill Finish, Black, White Standard Length: 6.5m Cover ends of Multiwall sheets. To be used in conjunction with End Cap Gasket.



Multiwall data

	Clear	Grey Tint	Bronze Tint	Opal	Platinum
Light Transmission	86%	9%	22%	16%	11%
Heat transmission	76%	24%	30%	29%	16%
Solar Heat Gain	0.789	0.473	0.516	0.343	0.327
Shading Co-efficient	0.907	0.544	0.593	0.394	0.376

End Cap Gasket

Colour: Black Standard Gauges: 10mm Standard Length: 10m rolls Seal and secure ends of Multiwall sheets.

To be used in conjunction with Aluminium End Cap.

H-Bar Gasket

Breather Tape

Length: 24m

Sealing Tape

Length: 50m

Prevent moisture and dust from

entering Multiwall flutes.

Colour: Black Standard Gauges: 10mm Standard Length: 20m rolls Seal and secure edges of Multiwall sheets. To be used in conjunction with H-Bars and Edge Bars.



Please refer to the Laserlite website www.laserlite.com.au for full details on:

- 15 Year Product Warranty

- Installation & Safety
- Product Technical data

Colours depicted in this brochure are representations offered as a guide only and should not form the basis of a colour selection. Slight colour variation may occur between production runs. Transmitted light and colour may vary in intensity depending on weather conditions. The information contained in this brochure is to the best of our knowledge accurate but all recommendations are made without any warranty whatsoever, since the conditions of use are beyond our control. This brochure cancels and supersedes all previous publicised information. The company reserves the right to alter and revise, without notice, the information contained herein.



Polycarbonate Roofing 51 Steel Street Capalaba Qld

sales@polycarbonate.com.au

1800 506 454

