



CONCEALED HINGE


W/ 3D ADJUSTMENT

FEATURES:

- Can be used on interior or exterior doors.
- These hinges allow three-dimensional adjustment (depth, vertical and horizontal). This means the door can be aligned with the wall to perfection where there is frameless architectural.
- Recommended maximum opening angle of 120 degrees.
- Hinge reversible for right/left doors.
- Comes with Self-lubricating anti-friction washers.


COMPONENTS:

- 1x 5970 3D Hinge
- 8x Fixing Screws
- 4x Covers
- 1x Allen Key



WARNINGS





- Not recommended to use door closers with restraint system.
- The adjustments in 3 axes must be carried out on one axis at a time.
- Make small adjustments to the adjusting screws alternating hinge on hinge



CONCEALED HINGE


W/ 3D ADJUSTMENT

MEASUREMENTS





CONCEALED HINGE W/ 3D ADJUSTMENT

DOOR SPECIFICATIONS




Distribution






CONCEALED HINGE W/ 3D ADJUSTMENT

ADJUSTMENT



- ① • Depth adjustment. Loose the 2 screws of each hinge.
 - Adjust the position of the door.
 - Tighten all screws, torque 3 N/m. /
- ② • Vertical adjustment. Loose the 2 screws of each hinge.
 - Place a shim in the lower part of the door with the desired gap.
 - Tighten all screws, torque 3 N/m. /
- ③ • Horizontal adjustment. Loose the screws (3.1) of each hinge. Turning alternately the screws (3) in order to achieve the desired gap. To lock adjustment tighten all the Screws (3.1) Torque 3 N/m. /

CUT OUT



WARNING R = 1MM (MIN.)

