Corrolink 1000 Minimum Fall: 3° 1000mm Cover Width

Versiciad STRUCTURAL INSULATED PANELS

Quata/Ordar Earm

Minimum Fall: 3º 1000		Quote/	Order	Form			
Date: / /	Order No	.:			Job Name:		
Company Name:					ABN:		
Order Contact Name:				Order C	ontact Phone:		
Order Contact Email:				Date o	order required:		
Invoice Address:				State:		Post Code:	
Delivery Address:				State:		Post Code:	
Site Contact:				Site C	ontact Phone:		
1. Corrolink 10)00 Quot	e / Order	Q	uote:		Order:	
2. Thickness							
Core Thickness:		50mm	75mm	100mm	125mm	150mm	180mm
Overall Thickness:		67mm	92mm	117mm	142mm	167mm	197mm
3. Roof Colou	r						
Ipine White Off White (*Surfmist)		Gull Grey (*Shale Grey)	Birch Grey (*Dune)	, ,	smin Brown (*Jasper) (*Manor Re		
						Corrosion Resista	nt Option
Gulf Wallaroo Basa (*Gully) (*Wallaby) (*Basa		e+ Caulfield Green) (Cottage Green) +Limited W	(Ironstone) (Monume		Aunicote (Moni (*Moni		te Armour Grey
			÷		UniCote	Coastal™ only available	2

*Equivalent colour names are trade marks or registered trade marks of BlueScope Steel Limited and used only for comparison. Colour and finish swatches are provided as an indication only and may not be an actual representation of colour or finish. We recommend checking your chosen colour and finish against an actual sample of the product before purchasing.

4. Ceiling				
Pearl White	Cream	Merino	^UniCote Coastal™Pearl White	Timber Effect
				(Luxline only)
Smooth Embossed Micraline Luxline	Smooth Micraline Luxline	Smooth Micraline Luxline	Smooth Micraline Luxline	Golden Oak
			Only available with UniCote Coastal™ton skin	- Content Out

Additional LM charge applies UniCote Coastal & Timber Effect, refer pricelist.

with UniCote Coastal[™] ceiling skin.

5. Panel Quantities:

Quantity @		Top Skin Length	Standard Configurati 60mm Gutter Cutback (From	Cover		
	@	Top Skin Length Min - 1500mm Max - 10000mm	Alternatively, pla			
			Gutter Cutback (Front) Specify Size (mm)	Cutback (Rear) Specify Size (mm)	Lap (Right or Left)	Width
	@					1000mm
	@					1000mm
	@					1000mm
	@					1000mm
	@					1000mm
	@					1000mm
	@					1000mm

Versicad Structural INSULATED PANELS

Skylight Strip Order Form

1. Skylight Kit Combinations (Includes materials to install 1 x skylight per kit)						
Туре	Details	Qty. Cut to Length				
Corrolink 1000 - 4m Kit	Top Fibreglass Strip Twinwall Bottom Diffuser Strip 2 x 4000mm T-Bars Foam Infill Strip Stormtite Stitching Screws Rivets Twinwall Sealer Tape					
Corrolink 1000 - 6m Kit	Top Fibreglass Strip Twinwall Bottom Diffuser Strip 2 x 6000mm T-Bars Foam Infill Strip Stormtite Stitching Screws Rivets Twinwall Sealer Tape					
Corrolink 1000 - 8m Kit	Top Fibreglass Strip Twinwall Bottom Diffuser Strip 4 x 4000mm T-Bars Foam Infill Strip Stormtite Stitching Screws Rivets Twinwall Sealer Tape					

Alternatively, you can order items required individually below

2. Fibreglass Top & Twinwall Bottom			3. Accessories					
Type	Length	Qty.	Cut to Length (please specify length required)	Туре		Qty.	Туре	Qty.
	4m*			Corrolink 1000 Foam (Strip: 1 x per skylig			Twinwall Sealer Tape (50m Roll)	
Corrolink 1000 Top Fibreglass Strip	6m*			Rivets, White - 100 pack			Stitching Screws - 50 pack	
	8m*			3.2mm dia x 9.5mm			Surfmist Storm-Tite 25mm	
Twinwall Diffuser Bottom Strip	4m*			Aluminium T-Bar 4m Silicone: Clear/White White - 40 x 50mm 6m (Please Circle)		Silicone: Clear/White (Please Circle)		
	6m*			Corrolink 1000 Accessory Bag: Foam Infill Strip 35 x Stormtite Stitching Screws 60 x Rivets 1m Twinwall Sealer Tape				
	8m*							
*Please note: you will be purchasing full lengths. We will cut these to your required lengths and you will be provided with any offcuts.								

What you need:

- Fibreglass profiled top strip (4m, 6m & 8m only) cut to match overall top sheet length, if required
- Twin wall bottom diffuser ceiling strip (4m, 6m & 8m only) cut to match ceiling length, if required
- T-bar aluminium extrusions (4m & 6m only) require 2 x T-Bars per light strip, either side of bottom diffuser strip
- Twin wall seal tape require 460mm for each Skylight
- Foam infills (Spacemaker/Versalink 1000 = 2 piece set per skylight, Corrolink1000 = 1 piece per skylight, cut to size onsite)
- Stormtite Screws fixed through profile/crest at 600mm centres, along both sides of the fibreglass profiled top strip
- Blind Rivets fixed through T-Bar at 300mm centres
- Silicone run bead of silicone along top of horizontal section of T-Bar prior to pressing Twinwall into place and along Z Flashing prior to pressing foam infill into place

Please request and review engineering specifications prior to ordering skylights