



# Leak-Seal Tape

Self Stick Tape Consisting of a Waterproof Compound on a Reinforcing Fabric

## PRODUCT DESCRIPTION

Duram Leak-Seal Tape is a unique waterproofing membrane/reinforcing fabric combination with a special 1mm (approx.) self-adhesive waterproofing compound. Used in conjunction with Duram waterproofing membranes, it provides the ultimate waterproofing solution in waterproofing and sealing joints, corners and cracks. Duram Leak-Seal Tape is simple to apply, is quick, saves time, money and importantly provides the ultimate in waterproofing technique, and long-term reliability and protection.

## USAGE/PURPOSE

- Waterproofs and seals corners, joints, cracks and gaps.
- Duram Leak-Seal Tape should be used in conjunction with Duram waterproofing membranes for ultimate waterproofing protection.

## FEATURES & BENEFITS

- Duram Leak-Seal Tape is a waterproofing applicator's best friend. It provides the best solution to long-term waterproofing of joints, cracks and corners, saves time, effort and money.
- Duram membranes can be applied directly to Duram Leak-Seal Tape and eliminates the need to reinforce the membrane.
- Peel and stick.
- Has a tough, flexible and technically advanced waterproof backing.
- Gives greater protection than conventional methods of waterproofing.
- Provide double the waterproofing protection to critical areas.

## PACKAGING

- 80mm x 15m
- 150mm x 15m

## COLOUR

Off-White matting with a grey waterproof backing.

## STORAGE

Store in cool, dry and protected area.

## COVERAGE/YIELD

Not applicable.

## LIMITATIONS

Surfaces must be even and smooth to allow a good bond. Duram Leak-Seal Tape is not recommended for surfaces that are rough, pebbled, textured, spiky or similar.

## SUITABLE SURFACES

- Duram Leak-Seal Tape is suitable over clean, primed, even, and relatively smooth building surfaces.
- Concrete
- Render
- Block & Brick work
- CFC Sheeting
- Plaster Board
- Fibre Board
- Metal
- Timber
- Fibre-Glass Surfaces



## SURFACE PREPARATION

Good preparation is essential. Surfaces must be sound, stable, dry, clean and free of contaminants, dust, dirt, loose, flaking, friable material and substances that may diminish adhesion.

## PRIMING

- Prime surfaces with Duram Primeseal MC (or other suitable waterproofing primer as required for the Duram waterproofing membrane to be used) and allow to dry.
- To corners and joints, apply a flexible polyurethane joint sealant in the usual manner. The Duram Leak-Seal Tape can be applied directly and immediately over the sealant provided that the bead of sealant is no more than 10mm wide.

## APPLICATION

- Suitable Duram waterproofing membranes include: Duram Multithane, Duram 195, Azcothane Range, Durabit Range, Cristoflex, Pondseal & Supreme.
- Peel and stick the Duram Leak-Seal Tape, centred over the joint, crack or corner (Overlaps should be at least 100mm).
- It is important that pressure be applied uniformly to the entire areas of the tape to ensure a good bond.
- Duram Leak-Seal Tape can be applied over the wet polyurethane sealant provided that the bead of sealant is no more than 10mm wide.
- As soon as the tape is installed the Duram membranes can be applied over it. Coat over the Duram Leak-Seal Tape with a suitable Duram waterproofing membrane extending to the substrate as would usually be done or required for that product. Refer to the product data sheet.

## CURING

Drying and curing of the product is affected by type, dryness and porosity of the surface, temperature, humidity, ventilation, climate conditions and application technique and therefore drying and curing can only be given as a guide.

## TILING, TOPPING OR TOP COATING

After installation and application of the waterproofing membrane the area can be tiled, topped and coated. Refer to the data sheet of the waterproofing membrane.

## CLEAN UP

Not applicable.



## SPECIFICATION

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement. The applicator or contractor must use their skill, knowledge, and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the company in writing.

## HEALTH & SAFETY PRECAUTIONS

Duram Leak-Seal Tape is considered safe to use if used as intended. The Safety Data Sheet (SDS) must be read and understood prior to use.

## CONDITIONS OF USE AND DISCLAIMER

The information contained in this TDS is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the TDS in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

## TREMCO CPG AUSTRALIA

Duram a division of Tremco CPG Australia  
ABN: 25 000 024 064  
12/4 Southridge Street  
Eastern Creek, NSW 2766

P: (02) 9624 4077

F: (02) 9624 4079

E: [duram@duram.com.au](mailto:duram@duram.com.au)