

PVC PRIMING FLUID

SOLVENT BASED CLEANER & PRIMER FOR PVC PIPES & FITTINGS

3 January 2018

YOUR SMART ADVANTAGES

- WaterMark certified as per the Plumbing Code of Australia.
- Conforms to requirements specified in AS/NZS 3879 when used in conjunction with Bostik PVC Pipe cement Type N & Type P solvent cements.
- Suitable for water potable applications – meets AS/NZS 4020
- Unique, easy to use 'dauber' applicator included in cap (1L and under)
- Colour coded packaging for easy product selection
- Ready for use – no mixing required
- Good application viscosity; easily applied with minimal dripping

USES

- Use prior to application of both Type N & Type P **Bostik PVC Pipe Cements**

PRODUCT CHARACTERISTICS

Colour	Red or Clear
Viscosity	Thin; water-like
Composition	Solvent
Application temperature	10 to 30°C

Product codes

125mL Red	30840489
250mL Red	30840469
500mL Red	30840470
1L Red	30840471
4L Red	30840472
500mL Clear	30840473
4L Clear	30840494

Note: All containers 1 litre and less have an applicator dauber included in the cap.

DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com.au or by scanning the relevant QR code on pack.

BEFORE APPLICATION

- 1) Verify that the cement is suitable for the pipe and fitting materials being used.
- 2) Check temperatures where application will take place:
 - a) Cements take longer to set in cold weather. Allow extra time for curing. Do not try to speed up the cure by artificial means – this could cause bubbling and porosity in the cement film.
 - b) Solvents evaporate faster in warm and windy weather. Work quickly to avoid the cement drying before the joint is assembled. Avoid working in direct sunlight and on warm pipes. It is recommended that storage of materials and application should be in shaded areas. Ideal application temperatures are between 10°C and 30°C out of direct sunlight.
- 3) Shake the cement bottle well before use.
- 4) Ensure appropriate personal protective safety equipment is worn when using the solvent cement/priming fluid.
- 5) **DO NOT** mix any additives to the priming fluid or pipe cement.
- 6) Do not use gelled or lumpy cement. It should be the consistency of syrup.
- 7) Coloured cements and priming fluids will leave a permanent stain. Avoid spills. The stain may fade over time or after prolonged exposure to direct sunlight.

APPLICATION

1. Jointing procedure must be in compliance with the most current edition of AS/NZS 2032: Installation of PVC pipe systems.
2. Cut the end of the pipe square and remove all burrs and sharp edges from the inside and outside of the pipe.
3. Check the dry fit of the pipe and fitting before priming fluid/cement application. Check and ensure for proper interference fit.
4. With the pipe fully engaged in the fitting, mark the pipe with a witness mark at a distance equal to full fitting depth. Use a pencil to mark the pipe. Do not score the pipe. The priming fluid and cement must be coated slightly beyond the witness mark on the pipe.

BOSTIK PVC PRIMING FLUID

5. Ensure the pipes and fittings are dry and clean. Wipe any moisture and dirt off the outside surface of the pipe and inside surface of the fitting with a CLEAN rag. Do not use oily/dirty rags.
6. Thoroughly prime the inside of the fitting and external surface of the pipe with **Bostik PVC Priming Fluid**. Do not use dirty rags. Ensure 100% of the joint areas are covered with priming fluid. Ensure the application of the cement can occur immediately after primer application.
7. First, immediately apply an even coat of the pipe cement to the inside of the fitting then coat the external area of the pipe. Ensure 100% of the joint areas are covered with cement.
8. While the cement is still wet, immediately insert the pipe into the fitting ensuring to meet the witness mark. If the cement has dried do not continue and re-coat both the pipe and fitting. A dry joint will fail.
9. Firmly hold the assembled joint together for at least 1 minute to prevent the pipe from kicking out. Without disturbing the joint carefully wipe any excess cement from the joint and allow the assembly to sit undisturbed for 5 minutes.
10. Allow 24 hours before putting the joint into service.

Bonding of PVC-U sheet

1. Ensure PVC-U sheets are clean, dry and free from burrs.
2. Clean and prime both sheets with Bostik PVC Priming Fluid.
3. Apply cement in a thin even coat to both surfaces and whilst still wet, position together.
4. Weigh down or clamp until initial bonding takes place - approx 10 minutes (depending on weather conditions). While clamped wipe off any excess cement from the edges of the sheets before it dries.
5. Allow 24 hours to set before applying any stress or strain on the bond.

LIMITATIONS

- At temperatures greater than 30°C, rapid evaporation of solvent can occur before the solvents can penetrate the pipe surfaces. This may prevent a satisfactory bond and lead to a dry joint resulting in a failed bond. Always re-coat the pipe and fitting if the adhesive dries during application.
- When not in use ensure the lid is tightly secured on cement and priming fluid bottles. Evaporation of the solvent will affect the performance of the product.
- This product is not suitable for use in hot water systems.

- Application to larger diameter pipes may require a larger brush than that supplied. If a small brush is used on large diameter pipes and fittings, application time and full coverage of the pipe and fitting can take too long resulting in dry joints.

STORAGE AND SHELF LIFE

This product has a shelf life of 5 years from the date of manufacture when stored in the original, unopened container at normal room conditions. Ensure the lid is tightly secured on cement and priming fluid bottles when not in use to prevent solvent escaping.

ANCILLARY MATERIALS

Bostik PVC Priming Fluid must always be used for cleaning and priming substrates prior to application of Bostik PVC Pipe Cement.

VOC INFORMATION

GBCA Technical Clarification Statement PVC Pipe Cements IEQ-13, Clarification No. 43 – Published October 2009

Pipe cements are not relevant to the VOC credit as they have little influence on indoor air quality. Plumbing pipes are usually installed some time prior to building occupation and any residual of solvent will be negligible by the time the building is sealed and occupied. In addition, plumbing pipes are not a major component of an individual fit out or building, plumbing cements are minor in quantity in the indoor fit out when compared to adhesives used in countless other indoor applications.

Refer to Green Building Council Australia website for further details www.gcba.org.au

HEALTH AND SAFETY

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at www.bostik.com.au

BOSTIK HOTLINE

Smart help 1800 898 551



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com/au